

**GTIN** 



CO133T - Lincat
Convector Touch Electric
Counter-top Convection
Oven - W 610 mm - D 750
mm - 3.0 kW

Able to roast, braise, bake and reheat, a C0133T Convector convection oven is a powerful addition to any commercial kitchen.

- Touchscreen control with easy-to-use icon-driven menu selections
- Easy-view traffic light status see the status of the oven at a glance, even in the noisiest kitchens
- Space for 24 programs with up to four stages, which can be adjusted individually
- Up to four-stage phased cooking for perfect results - set temperature, time, fan speed and humidity injection for each stage
- Even heat distribution thanks to electronically controlled two-speed, bi-directional fan
- Five levels of humidity injection
- Nine-hour on-screen timer, with electronic buzzer, and flashing oven lamps to indicate that cycle has finished

#### **Specifications Power and Performance Summary** Total Power kW **Brand** 3.0 Range Convector Temperature Range °C 30-260 Series **IP Rating** IP23 Touch **Power Type** Electric **Controls Position** Right hand side **Unit Type Temperature Control** Electronic Counter-top Available in UK Only Timer Range mins 1-540 **UK Warranty** 2 Years Parts and Labour Warranty Oven Rating kW 2.8 **Export Warranty** Contact your local dealer

5056105118251



#### **Key Specifications**

Stackable Yes (with optional kit) Feet Height/Type 55mm/adjustable

Continuous Plug-In Door Seal Removable Inner Door Glass Yes **Handle Type** Grab Vented Door Yes Reversible Door Νn

**Door Type** Drop down **Number of Cooking Phases** 4 **Phased Cooking** Yes

Shelf Timer(s) (Number) Yes(4) Grill Element/Mode No **Core Temp Probe** No Steam Injection Yes Fan(s) Speed 2

Fan(s) Type Bi-Directional

Number of Fan(s) **Euronorm Compatible** No **Sheet Pan Compatible** Yes Removeable Shelf Guides Yes **Manual Mode** Yes Programmable Yes

**Number of Programs** 24 (4 stages) **Timer Type** Touchscreen **Display Type** Touchscreen

Number of Shelves included 3 **Number of Shelf Positions** 3

Type of Lighting Halogen Bulb Construction/Finish 304 S/S cavity **GN Compatible** 

Yes

Capacity

**Gastronorm Capacity** 3 x GN2/3 Shelf Spacing mm 80

**Sheet Pan Capacity** 3 x 460 mm x 330 mm

**Capacity Litres** 

Weights and Dimensions		Supply Connections	
Unit Height (External) mm	645	Requires Installation	No
Unit Width (External) mm	610	Requires Electrical Supply	Yes
Unit Depth (External) mm	750	UK 3 Pin Plug	Yes
Height (Internal) mm	308	Requires Hardwiring	No
Width (Internal) mm	490	Electrical Supply Rating Watts	3,000
Depth (Internal) mm	370	Single Phase Amps	13.0
Shelf Dimensions Width mm	460	Single Phase Voltage	230
Shelf Dimensions Depth mm	325	Water Connection Pressure Bar	2.0-6.0
Net Weight Kg	62.1	Drain Connection	No
		Water Connection	3/4" BSPT
		USB Port	Yes

## **Shipping**

Packed Weight Kg 72.2 Packed Height cm 81.5 Packed Width cm 70 Packed Depth cm 95

## **Available Accessories**


ACIK04 Water Treatment Filter Kit


CO100/FS Lincat Convector Floor Stand for C0133M/C0133T Convection Ovens - with 4 Runners - W 610 mm


CO100/LFSK Lincat Convector Low Floor Stand and Stacking Kit for C0133M/C0133T Convection Ovens - with 1 Runner - W 610 mm

# **Technical Picture**











**Lincat Limited** 

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

**Company No:** 2175448

A member company of

**Customer Care** 

**Tel:** +44 1522 875500

Email: care@lincat.co.uk

**Export Customers** 

**Tel:** +44 1522 875536

Email: export@lincat.co.uk

**Opening Hours** 

Monday - Friday:

8.30am - 5pm