



CO223T - Lincat
Convector Touch Electric
Counter-top Convection
Oven - W 810 mm - D 850
mm - 3.0 kW

Able to roast, braise, bake and reheat, a CO223T Convector convection oven is a powerful addition to any commercial kitchen.

- 2 x GN1/1 capacity
- Touchscreen control with easy-to-use icon-driven menu selections
- Easy-view traffic light status see the status of the oven at a glance, even in the noisiest kitchens
- Space for 24 programs with up to four stages, which can be adjusted individually
- Up to four-stage phased cooking for perfect results - set temperature, time, fan speed and humidity injection for each stage
- Even heat distribution thanks to electronically controlled two-speed, bi-directional fan
- Five levels of humidity injection
- Nine-hour on-screen timer, with electronic buzzer, and flashing oven lamps to indicate that cycle has finished

Specifications Power and Performance Summary Total Power kW **Brand** 3.0 Range Convector Temperature Range °C 30-260 Series **IP Rating** IP23 Touch **Power Type** Electric **Controls Position** Right hand side **Unit Type Temperature Control** Electronic Counter-top Available in UK Only Timer Range mins 1-540 **UK Warranty** 2 Years Parts and Labour Warranty Oven Rating kW 2.8 **Export Warranty** Contact your local dealer **GTIN** 5056105118275



Key Specifications Capacity Stackable Yes (with optional kit) **Gastronorm Capacity** 2 x GN1/1 **Euronorm Capacity** Feet Height/Type 2 x 600 mm x 400 mm 55mm/adjustable Continuous Plug-In Door Seal Shelf Spacing mm Yes **Removable Inner Door Glass** Yes **Sheet Pan Capacity** 2 x 660 mm x 460 mm **Handle Type Capacity Litres** 96.0 Grab Vented Door Yes Reversible Door Νn Door Type Drop down **Number of Cooking Phases** 4 **Phased Cooking** Yes Shelf Timer(s) (Number) Yes(4) Grill Element/Mode No **Core Temp Probe** No Steam Injection Yes Fan(s) Speed 2 Fan(s) Type Bi-Directional Number of Fan(s) **Euronorm Compatible** Yes **Sheet Pan Compatible** Yes Removeable Shelf Guides Yes **Manual Mode** Yes Programmable Yes **Number of Programs** 24 (4 stages) **Timer Type** Touchscreen **Display Type** Touchscreen **Number of Shelves included** 2 **Number of Shelf Positions** 2 Type of Lighting Halogen Bulb Construction/Finish 304 S/S cavity **GN Compatible** Yes

Weights and Dimensions		Supply Connections	
Unit Height (External) mm	645	Requires Installation	No
Unit Width (External) mm	810	Requires Electrical Supply	Yes
Unit Depth (External) mm	850	UK 3 Pin Plug	Yes
Height (Internal) mm	308	Requires Hardwiring	No
Width (Internal) mm	690	Electrical Supply Rating Watts	3,000
Depth (Internal) mm	470	Single Phase Amps	13.0
Shelf Dimensions Width mm	660	Single Phase Voltage	230
Shelf Dimensions Depth mm	425	Water Connection Pressure Bar	2.0-6.0
Net Weight Kg	80	Drain Connection	No
		Water Connection	3/4" BSPT
		USB Port	Yes

Packed Weight Kg 92.1 Packed Height cm 81.5 Packed Width cm 88 Packed Depth cm 100

Available Accessories

ACIK04 Water Treatment Filter Kit


CO200/FS Lincat Convector Floor Stand for CO223M/CO235M/CO235T Convection Ovens - with 4 Runners - W 810 mm


CO200/LFSK Lincat Convector Low Floor Stand and Stacking Kit for C0223M/C0223T/C0235M/C0235T Convection Ovens - with 1 Runner - W


810 mm



Technical Picture









Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm