



CO343M - Lincat Convector Manual+ Electric Counter-top Convection Oven - W 660 mm - D 740 mm - 3.0 kW

Able to roast, braise, bake and reheat, a CO343M Convector convection oven is a powerful addition to any commercial kitchen.

- ✓ 4 x GN1/1 capacity
- Easy-to-use knob-driven control, and electronic fan control
- Mechanical temperature control from 60° to 260° C
- Even heat distribution thanks to electronically controlled two-speed, bi-directional fan
- Two fan speeds standard for general use and slow for delicate items
- 120 minute count down timer with electronicallycontrolled buzzer
- Oven lamps flash when cook cycle has finished see when your food is done even in the busiest
- Side opening door

Specifications						
Summary		Power and Performance				
Brand	Lincat	Total Power kW	3.0			
Range	Convector	Temperature Range °C	60 - 260			
Power Type	Electric	IP Rating	IP23			
Unit Type	Counter-top	Controls Position	Right hand side			
Available in UK Only	No	Temperature Control	Mechanical			
UK Warranty	2 Years Parts and Labour Warranty	Timer Range mins	1 - 60			
Export Warranty	Contact your local dealer	Oven Rating kW	2.8			
GTIN	5056105121404					



Key Specifications Capacity Feet Height/Type 55mm/adjustable **Gastronorm Capacity** 4 x GN1/1 Continuous Plug-In Door Seal Shelf Spacing mm 85 Yes Removable Inner Door Glass **Sheet Pan Capacity** 4 × 460 × 330 No **Handle Type** Grab **Capacity Litres** Vented Door Yes Reversible Door No **Door Type** Left Hinaed **Number of Cooking Phases** No **Phased Cooking** No Shelf Timer(s) (Number) Grill Element/Mode No **Core Temp Probe** No Steam Injection No Fan(s) Speed 2 Fan(s) Type Bi-Directional Number of Fan(s) **Euronorm Compatible** No **Sheet Pan Compatible** Removeable Shelf Guides Yes **Manual Mode** Yes Programmable No Timer Type Mechanical Number of Shelves included 4 **Number of Shelf Positions** 4 Type of Lighting Halogen Construction/Finish 430 S/S cavity

Weights and Dimensions		Supply Connections	Supply Connections	
Unit Height (External) mm	600	Requires Installation	No	
Unit Width (External) mm	660	Requires Electrical Supply	Yes	
Unit Depth (External) mm	695	UK 3 Pin Plug	Yes	
Height (Internal) mm	398	Requires Hardwiring	No	
Width (Internal) mm	330	Electrical Supply Rating Watts	3000	
Depth (Internal) mm	550	Single Phase Amps	13	
Shelf Dimensions Width mm	530	Single Phase Voltage	230	
Shelf Dimensions Depth mm	325	USB Port	No	
Net Weight Kg	68			
Shipping				
Packed Weight Kg	83.7			
Packed Height cm	81.5			
Packed Width cm	88			

Available Accessories

Packed Depth cm

GN Compatible

Yes


100


CO300/FS Lincat Convector Floor Stand for CO343M/CO343T Convection Ovens - with 4 Runners - W 660 mm


CO300/LFSK Lincat Convector Low Floor Stand and Stacking Kit for CO343M/CO343T Convection Ovens - with 1 Shelf - W 660 mm

Technical Picture











Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm